



The Public Health and Safety Organization

## NSF Product and Service Listings

These NSF Official Listings are current as of **Thursday, May 12, 2016** at 12:15 a.m. Eastern Time. Please [contact NSF International](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: <http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=34570&Standard=061&>

---

## NSF/ANSI 61 Drinking Water System Components - Health Effects

**NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#). Click here for the definitions of [Water Contact Temperatures denoted in these Listings](#).**

---

### The Euclid Chemical Company

3835 State Route 72

Kirkland, IL 60146

United States

815-522-3394

[Visit this company's website \(http://www.euclidchemical.com\)](http://www.euclidchemical.com)

**Facility :** Kirkland, IL

### Protective (Barrier) Materials

Trade Designation	Water Contact Size Restriction	Water Contact Temp	Water Contact Material
<b>Coatings - Tank</b>			
Hey'Di K-11/Hey'Di SB[1]	>= 1000 gal.	CLD 23	CMNT
Tamoseal Ultra/Tamoseal Ultra Liquid[1]	>= 1000 gal.	CLD 23	CMNT

[1] Colors: Gray, white

Number of Coats: 2

Sequence of Coats: N/A

Maximum Field Use Dry Film Thickness (in mils): 60

Maximum Thinner: None

Recoat Cure Time and Temperature: 24 hours at 75°F

Final Cure Time and Temperature: 7 days at 75°F

Special Comments: Apply to concrete at a rate of 0.25 lb. mixed slurry per square foot.  
Mix 1:5 Hey'Di SB Bonding with water then mix that at 50 lb. Hey'Di K-11 to 2 gallons of mixed SB Bonding.

---

Number of matching Manufacturers is 1

Number of matching Products is 2

Processing time was 1 seconds