

Revision Date: 07/30/2015

# SAFETY DATA SHEET

# 1. Identification

Material name: SUPER WALL-PRO PORTLAND GRAY 5 GAL MTO

Material: 1510E690105

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110

US

Contact person:EH&S DepartmentTelephone:216-531-9222

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

100 %

## 2. Hazard(s) identification

### **Hazard Classification**

#### **Health Hazards**

Acute toxicity (Inhalation - dust and Category 4

mist)

Carcinogenicity Category 1A

**Unknown toxicity - Health** 

Acute toxicity, oral 33.87 %
Acute toxicity, dermal 38.8 %
Acute toxicity, inhalation, vapor 99.95 %
Acute toxicity, inhalation, dust or mist 73.19 %

**Environmental Hazards** 

Acute hazards to the aquatic Category 3

environment

**Unknown toxicity - Environment** 

Acute hazards to the aquatic 64.52 % environment

Chronic hazards to the aquatic

environment

### **Label Elements**

# **Hazard Symbol:**



Revision Date: 07/30/2015



Signal Word: Danger

**Hazard Statement:** Harmful if inhaled.

May cause cancer. Harmful to aquatic life.

Precautionary Statement: Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal

protective equipment as required.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for

breathing. Call a POISON CENTER/doctor if you feel unwell.

Storage: Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

# 3. Composition/information on ingredients

# Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Titanium dioxide	13463-67-7	3 - 7%
Propylene glycol	57-55-6	1 - 5%
Zinc oxide	1314-13-2	1 - 5%
Cellulose	9004-34-6	1 - 5%
Clay	1332-58-7	0.1 - 1%
Magnesite	546-93-0	0.1 - 1%
Heavy paraffinic distillate	64741-88-4	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%
Amorphous silica	7631-86-9	0.1 - 1%
Ethylene glycol	107-21-1	0.1 - 1%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures



Revision Date: 07/30/2015

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

**Inhalation:** Move to fresh air.

**Skin Contact:** Wash skin thoroughly with soap and water. Get medical attention if

symptoms occur.

**Eye contact:** Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.



Revision Date: 07/30/2015

**Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

# 7. Handling and storage

**Precautions for safe handling:** Do not handle until all safety precautions have been read and understood.

Obtain special instructions before use. Use personal protective equipment as required. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities:

Store locked up.

## 8. Exposure controls/personal protection

#### **Control Parameters**

**Occupational Exposure Limits** 

	Ī		
Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	STEL	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Zinc oxide - Fume.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Cellulose - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)





Revision Date: 07/30/2015

Clay - Respirable fraction.				(02 2006)
Fraction.	Clay - Respirable	TWA	2 ma/m3	
PEL		1 ***	2 mg/mo	
Contaminants (29 CFR 1910.1000) (02 2006)		DEI	5 ma/m3	
Clay - Total dust.		FEL	5g	
Contaminants (29 CFR 1910.1000) (02 2006)				
Contaminants (29 CFR 1910.1000) (02 2006)	Clay - Total dust.	PEL	15 mg/m3	
Magnesite - Total dust.       PEL       15 mg/m3       US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)         Magnesite - Respirable fraction.       TWA       5 mg/m3       US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)         Heavy paraffinic distillate - Inhalable fraction.       TWA       5 mg/m3       US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)         Heavy paraffinic distillate - Mist.       PEL       500 ppm       2,000       US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)         Heavy paraffinic distillate - Mist.       PEL       5 mg/m3       US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)         Aluminum oxide - Respirable fraction.       PEL       5 mg/m3       US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)         Aluminum oxide - Total dust.       PEL       15 mg/m3       US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)         Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.       TWA       0.025 US. ACGIH Threshold Limit Values (2011)         Crystalline Silica (Quartz)/ Silica Sand - Respirable.       TWA       0.1 mg/m3       US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)         Crystalline Silica (Quartz)/ Silica Sand - Total dust.       TWA       0.3 mg/m3       US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)         Crystalline S	j		G	Contaminants (29 CFR 1910.1000)
Contaminants (29 CFR 1910.1000) (02 2006)				
	Magnesite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
Magnesite - Respirable   FeL   5 mg/m3   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   Heavy paraffinic distillate - Inhalable fraction.   Heavy paraffinic distillate - Inhalable fraction.   PEL   500 ppm   2,000   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   Heavy paraffinic distillate - Mist.   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-3 (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-3 (29 CFR 1910.1000) (20 2006)   US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)   US. OSHA Table Z-				
Fraction.   Contaminants (29 CFR 1910.1000) (02 2006)				
Heavy paraffinic distillate - Inhalable fraction.  Heavy paraffinic distillate - Inhalable fraction.  Heavy paraffinic distillate - Mist.  Heavy paraffinic distillate - Mist.  Heavy paraffinic distillate - Mist.  PEL 500 ppm 2,000 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  Heavy paraffinic distillate - Mist.  PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  Aluminum oxide - Respirable fraction.  PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  Aluminum oxide - Total dust.  PEL 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  Crystalline Silica (Quartz/) Silica Sand - Respirable fraction.  Crystalline Silica (Quartz/) Silica Sand - Respirable.  TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz/) Silica Sand - Respirable.  TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz/) Silica Sand - TWA 0.3 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz/) Silica Sand - TWA 0.3 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz/) Silica Sand - Total dust.  Amorphous silica TWA 0.3 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz/) Silica Sand - Total dust.  Amorphous silica TWA 0.8 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Ethylene glycol - Ceiling 100 US. ACGIH Threshold Limit Values		PEL	5 mg/m3	
Heavy paraffinic distillate - Inhalable fraction.   February paraffinic distillate - Inhalable fraction.   February paraffinic distillate   PEL   S00 ppm   2,000 mg/m3   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)   US. OSHA Table Z-3 (29 CFR 1910.1000) (20 2006)   US. ACGIH Threshold Limit Values (2011)   US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	fraction.			
distillate - Inhalable fraction.         (2011)           Heavy paraffinic distillate         PEL         500 ppm         2,000 gm/m3         US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)           Heavy paraffinic distillate - Mist.         PEL         5 mg/m3         US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)           Aluminum oxide - Respirable fraction.         TWA         1 mg/m3         US. ACGIH Threshold Limit Values (2011)           Aluminum oxide - Total dust.         PEL         5 mg/m3         US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (22 2006)           Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.         TWA         0.025 mg/m3         US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (20 2006)           Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.         TWA         0.025 mg/m3         US. ACGIH Threshold Limit Values (2011)           Crystalline Silica (Quartz)/ Silica Sand - Total dust.         TWA         0.1 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Crystalline Silica (Quartz)/ Silica Sand - Total dust.         TWA         0.3 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Amorphous silica         TWA         0.3 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           TWA         0.8 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000				
Fraction		TWA	5 mg/m3	
Heavy paraffinic distillate   PEL   500 ppm   2,000 mg/m3   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)				(2011)
Description		DEL	500	
Heavy paraffinic distillate - Mist.		PEL		
Heavy paraffinic distillate - Mist.	distillate		mg/m3	
Aluminum oxide - Respirable fraction.	Hoove paraffinia	DEL	E ma/m2	
Aluminum oxide - Respirable fraction.  PEL  S mg/m3  US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  Aluminum oxide - Total dust.  PEL  15 mg/m3  US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.  Crystalline Silica (Quartz)/ Silica Sand - Respirable.  TWA  0.025  US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  US. ACGIH Threshold Limit Values (2011)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2011)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz)/ Silica Sand - Respirable.  TWA  0.1 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)		PEL	5 mg/m3	
Aluminum oxide - Respirable fraction.  PEL  5 mg/m3  US. ACGIH Threshold Limit Values (2011)  US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  Aluminum oxide - Total dust.  PEL  15 mg/m3  US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  US. OSHA Table Z-3 (29 CFR 1910.1000) (20 2006)  TWA  2.4  US. OSHA Table Z-3 (29 CFR 1910.1000) (20 200)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  0.1 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  0.3 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	distillate - Mist.			
Respirable fraction.	Aluminum ovide -	Τ\Λ/Δ	1 mg/m3	
PEL   5 mg/m3   US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)		1000	i ing/ino	
Aluminum oxide - Total dust.  PEL  15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.  Crystalline Silica (Quartz)/ Silica Sand - Respirable.  TWA  2.4 US. OSHA Table Z-3 (29 CFR 1910.1000) (2011)  TWA  2.4 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  US. ACGIH Threshold Limit Values (2011)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz)/ Silica Sand - TWA  0.3 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	respirable fraction.	DEL	5 mg/m3	
Aluminum oxide - Total dust.		PEL	o mg/me	
Aluminum oxide - Total dust.  PEL  15 mg/m3  US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)  Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.  Crystalline Silica (Quartz)/ Silica Sand - Respirable.  TWA  2.4  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  2.4  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  0.1 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz)/ Silica Sand - TWA  O.3 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz)/ Silica Sand - TWA  O.3 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  O.8 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Ethylene glycol - Ceiling				
Contaminants (29 CFR 1910.1000) (02 2006)   Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.   Crystalline Silica (Quartz)/ Silica Sand - Respirable Silica (Quartz)/ Silica Sand - Respirable.   TWA	Aluminum oxide - Total	PEL	15 mg/m3	
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.  Crystalline Silica (Quartz)/ Silica Sand - Respirable.  TWA  TWA  2.4 (US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  10.1 mg/m3  Crystalline Silica (Quartz)/ Silica Sand - Respirable.  TWA  10.1 mg/m3  Crystalline Silica (Quartz)/ Silica Sand - TWA  10.3 mg/m3  Crystalline Silica (Quartz)/ Silica Sand - Total dust.  Amorphous silica  TWA  20 millions of 1910.1000) (2000)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	dust.		· ·	Contaminants (29 CFR 1910.1000)
(Quartz)/ Silica Sand - Respirable fraction.         TWA         2.4 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Crystalline Silica (Quartz)/ Silica Sand - Respirable.         TWA         0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Crystalline Silica (Quartz)/ Silica Sand - Total dust.         TWA         0.3 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Amorphous silica         TWA         20 millions of particles per cubic foot of air         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           TWA         20 millions of particles per cubic foot of air         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           TWA         0.8 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Ethylene glycol -         Ceiling         100 US. ACGIH Threshold Limit Values				
Respirable fraction.  Crystalline Silica (Quartz)/ Silica Sand - Respirable.  TWA  TWA  1.1		TWA	0.025	US. ACGIH Threshold Limit Values
Crystalline Silica (Quartz)/ Silica Sand - Respirable.  TWA  TWA  D.1 mg/m3  Crystalline Silica (Quartz)/ Silica Sand - Particles per cubic foot of air  TWA  Crystalline Silica (Quartz)/ Silica Sand - Total dust.  Amorphous silica  TWA  TWA  D.1 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)			mg/m3	(2011)
(Quartz)/ Silica Sand - Respirable.         millions of particles per cubic foot of air         1910.1000) (2000)           TWA         0.1 mg/m3 per cubic foot of air         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Crystalline Silica (Quartz)/ Silica Sand - Total dust.         TWA         0.3 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Amorphous silica         TWA         20 millions of particles foot of air         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           TWA         0.8 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Ethylene glycol -         Ceiling         100 US. ACGIH Threshold Limit Values				
Respirable.  particles per cubic foot of air  TWA  0.1 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz)/ Silica Sand - Total dust.  Amorphous silica  TWA  0.3 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  0.8 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Ethylene glycol -  Ceiling  100  US. ACGIH Threshold Limit Values		TWA		
Der cubic foot of air				1910.1000) (2000)
TWA   0.1 mg/m3   US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)	Respirable.		•	
TWA  O.1 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Crystalline Silica (Quartz)/ Silica Sand - Total dust.  Amorphous silica  TWA  O.3 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  O.8 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Ethylene glycol -  Ceiling  TWA  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)				
1910.1000) (2000)   Crystalline Silica   TWA   0.3 mg/m3   US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)   Total dust.   Amorphous silica   TWA   20 millions of particles per cubic foot of air   TWA   0.8 mg/m3   US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)   Ethylene glycol -   Ceiling   100   US. ACGIH Threshold Limit Values   Crystalline   Comparison   Comparison				110 00114 T-bl- 7 0 (00 05D
Crystalline Silica (Quartz)/ Silica Sand - Total dust.         TWA         0.3 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Amorphous silica         TWA         20 millions of particles per cubic foot of air         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           TWA         0.8 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Ethylene glycol -         Ceiling         100		TWA	U.1 mg/m3	
(Quartz)/ Silica Sand - Total dust.         1910.1000) (2000)           Amorphous silica         TWA         20 millions of particles per cubic foot of air         1910.1000) (2000)           TWA         0.8 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Ethylene glycol -         Ceiling         100         US. ACGIH Threshold Limit Values	Crystallina Cilica	TVA/A	0.2 ma/m2	
Total dust.         20 millions of particles per cubic foot of air         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           TWA         0.8 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Ethylene glycol -         Ceiling         100         US. ACGIH Threshold Limit Values		IVVA	U.S mg/ms	
Amorphous silica  TWA  20 millions of particles per cubic foot of air  TWA  0.8 mg/m3  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  TWA  US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)  Ethylene glycol -  Ceiling  100  US. ACGIH Threshold Limit Values				1910.1000) (2000)
of particles per cubic foot of air         1910.1000) (2000)           TWA         0.8 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Ethylene glycol -         Ceiling         100         US. ACGIH Threshold Limit Values		TWA	20 millions	US OSHA Table 7-3 (29 CFR
per cubic   foot of air	, and pridas silida	1 7 7 / 1		
foot of air         TWA         0.8 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Ethylene glycol -         Ceiling         100         US. ACGIH Threshold Limit Values				.5.5.1555, (=555)
TWA         0.8 mg/m3         US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)           Ethylene glycol -         Ceiling         100         US. ACGIH Threshold Limit Values				
Ethylene glycol - Ceiling 1910.1000) (2000)  US. ACGIH Threshold Limit Values		Τ\Λ/Δ		US. OSHA Table Z-3 (29 CFR
Ethylene glycol - Ceiling 100 US. ACGIH Threshold Limit Values		1 4 4 7	2.299	
	Ethylene glycol -	Ceiling	100	





Revision Date: 07/30/2015

Chamical name	to en a	Eve same Lin	ait Values	Sauras
Chemical name	type	Exposure Lin		Source
Calcium carbonate - Total dust.	STEL		20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Propylene glycol - Aerosol.	TWAEV		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Propylene glycol - Vapor and aerosol, inhalable fraction.	TWAEV	50 ppm	155 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zinc oxide - Respirable.	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)





Revision Date: 07/30/2015

Zinc oxide - Respirable fraction.	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zinc oxide - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Fume.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cellulose - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cellulose - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cellulose	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cellulose - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Heavy paraffinic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Heavy paraffinic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Revision Date: 07/30/2015

Heavy paraffinic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

# Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

#### Individual protection measures, such as personal protective equipment

**General information:** Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists,

mechanical generation of dusts, drying of solids, etc.

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product.

# 9. Physical and chemical properties

#### **Appearance**

Physical state: liquid
Form: liquid
Color: Gray
Odor: Mild



Revision Date: 07/30/2015

Odor threshold: No data available.

**pH:** 9 - 10

Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.Flash Point:No data available.Evaporation rate:Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.33

Solubility(ies)

Solubility in water: Soluble

Solubility (other):

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

No data available.

No data available.

No data available.

Viscosity:

No data available.

## 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

**Possibility of Hazardous** 

Reactions:

No data available.

**Conditions to Avoid:** Avoid heat or contamination.

**Incompatible Materials:** Strong acids. Strong bases.

**Hazardous Decomposition** 

Thermal decomposition or combustion may liberate carbon oxides and

**Products:** other toxic gases or vapors.

# 11. Toxicological information

# Information on likely routes of exposure

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** May be harmful in contact with skin.

Revision Date: 07/30/2015

**Eye contact:** Eye contact is possible and should be avoided.

# Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** No data available.

Dermal

**Product:** ATEmix: 3,945.52 mg/kg

Inhalation

**Product:** ATEmix: 3.06 mg/l

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Calcium carbonate in vivo (Rabbit, 24 - 72 hrs): Not irritating

Titanium dioxide in vivo (Rabbit, 24 - 72 hrs): Not irritating

Propylene glycol (Human): Irritating

Zinc oxide in vivo (Rabbit, 24 - 72 hrs): Not irritating

Magnesite In vitro (Reconstituted Corneal Epithelium model, 10 min): Not irritating

Heavy paraffinic

distillate

in vivo (Rabbit, 24 hrs): Not irritating

Aluminum oxide in vivo (Rabbit, 24 hrs): Not irritating

Amorphous silica in vivo (Rabbit, 24 hrs): Not irritating

Ethylene glycol in vivo (Rabbit, 24 hrs): Not irritating

Respiratory or Skin Sensitization

**Product:** No data available.

Carcinogenicity

**Product:** No data available.



Revision Date: 07/30/2015

### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

Heavy paraffinic Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

distillate evaluation: Carcinogenic to humans.

Crystalline Silica (Quartz)/ Silica

Sand

Overall evaluation: Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

Heavy paraffinic Known To Be Human Carcinogen.

distillate

Crystalline Silica Known To Be Human Carcinogen.

(Quartz)/ Silica

Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.



Revision Date: 07/30/2015

# 12. Ecological information

### **Ecotoxicity:**

### Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Calcium carbonate LC 50 (Western mosquitofish (Gambusia affinis), 96 h): > 56,000 mg/l

Mortality

Titanium dioxide LC 50 (Mummichog (Fundulus heteroclitus), 96 h): > 1,000 mg/l Mortality

Propylene glycol LC 50 (Fathead minnow (Pimephales promelas), 96 h): 55,770 mg/l Mortality

Zinc oxide LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2,246 mg/l Mortality

Ethylene glycol LC 50 (Fathead minnow (Pimephales promelas), 96 h): 40,000 - 60,000 mg/l

Mortality

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Propylene glycol EC 50 (Water flea (Daphnia magna), 48 h): > 10,000 mg/l Intoxication

EC 50 (Water flea (Daphnia magna), 24 h): > 10,000 mg/l Intoxication LC 50 (Brine shrimp (Artemia salina), 24 h): > 10,000 mg/l Mortality

Zinc oxide LC 50 (Water flea (Daphnia magna), 48 h): 24.6 mg/l Mortality

Ethylene glycol LC 50 (Water flea (Daphnia magna), 24 h): 37,800 - 45,100 mg/l Mortality

LC 50 (Water flea (Daphnia magna), 24 h): > 10,000 mg/l Mortality LC 50 (Brine shrimp (Artemia sp.), 24 h): > 20,000 mg/l Mortality LC 50 (Brine shrimp (Artemia salina), 24 h): > 20,000 mg/l Mortality

LC 50 (Common shrimp, sand shrimp (Crangon crangon), 48 h): > 100 mg/l

Mortality

## Chronic hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental

result

Propylene glycol NOAEL (Pimephales promelas, 7 d): 11,530 mg/l experimental result

Zinc oxide NOAEL (Oncorhynchus mykiss, 30 d): 974 µg/l interpreted

Heavy paraffinic distillate NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

12/17



Revision Date: 07/30/2015

Aluminum oxide NOAEL (Pimephales promelas, 28 d): 4.7 mg/l experimental result

Ethylene glycol NOAEL (Pimephales promelas, 7 d): 15,380 mg/l experimental result

**Aquatic Invertebrates** 

**Product:** No data available.

**Toxicity to Aquatic Plants** 

**Product:** No data available.

**Persistence and Degradability** 

Biodegradation

**Product:** No data available.

**BOD/COD Ratio** 

**Product:** No data available.

**Bioaccumulative Potential** 

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Specified substance(s):

Ethylene glycol Crayfish (Procambarus), Bioconcentration Factor (BCF): 0.42 (Flow through)

Partition Coefficient n-octanol / water (log Kow)
Product:
No data available.

Specified substance(s):

Propylene glycol Log Kow: -0.92

Ethylene glycol Log Kow: -1.36

Mobility in Soil: No data available.

Other Adverse Effects: Harmful to aquatic organisms.

13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:



Revision Date: 07/30/2015

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

# 15. Regulatory information

# **US Federal Regulations**

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

#### CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

Ethylene glycol 5000 lbs. Ammonium hydroxide 1000 lbs. Ammonia 100 lbs.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

## **Hazard categories**

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

#### **SARA 302 Extremely Hazardous Substance**

Reportable

Chemical Identity quantity Threshold Planning Quantity

Ammonia 100 lbs. 500 lbs.

## **SARA 304 Emergency Release Notification**

Chemical Identity Reportable quantity

Zinc oxide

Ethylene glycol 5000 lbs. Ammonium hydroxide 1000 lbs. Ammonia 100 lbs.



Revision Date: 07/30/2015

#### SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Ammonia	500lbs
Calcium carbonate	500 lbs
Titanium dioxide	500 lbs
Propylene glycol	500 lbs
Zinc oxide	500 lbs
Cellulose	500 lbs
Clay	500 lbs
Magnesite	500 lbs
Heavy paraffinic distillate	500 lbs
Aluminum oxide	500 lbs
Crystalline Silica (Quartz)/	500 lbs
Silica Sand	
Amorphous silica	500 lbs
Ethylene glycol	500 lbs

## SARA 313 (TRI Reporting)

# **Chemical Identity**

Zinc oxide

## Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical Identity	Reportable quantity		
Ammonia	10000 lbs		
Ammonia	20000 lbs		

## **US State Regulations**

## **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

# US. New Jersey Worker and Community Right-to-Know Act

## **Chemical Identity**

Calcium carbonate
Titanium dioxide
Propylene glycol
Zinc oxide
Cellulose

# US. Massachusetts RTK - Substance List

## **Chemical Identity**

Calcium carbonate Titanium dioxide Zinc oxide Cellulose

Crystalline Silica (Quartz)/ Silica Sand

Ammonia



Revision Date: 07/30/2015

#### US. Pennsylvania RTK - Hazardous Substances

# **Chemical Identity**

Calcium carbonate Titanium dioxide Propylene glycol Zinc oxide Cellulose

### **US. Rhode Island RTK**

#### **Chemical Identity**

Zinc oxide

## Other Regulations:

Regulatory VOC (less water 71 g/l

and exempt solvent):

**VOC Method 310:** 2.87 %

**Inventory Status:** 

Australia AICS: One or more components in this product are

not listed on or exempt from the Inventory.

Canada DSL Inventory List: One or more components in this product are

not listed on or exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List:

One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory:

One or more components in this product are

not listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 07/30/2015

Japan ISHL Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

**Revision Date:** 07/30/2015

Version #: 1.0

Further Information: No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.