

**EUCON SRA - 275 GAL TOTE**Version 1.3  
REVISION DATE: 02/24/2007

Print Date 07/03/2007

**SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION****Product Information**Trade name : EUCON SRA - 275 GAL TOTE  
Product code : 010C 27Supplier : Euclid Canada  
2835 Grande-Allée  
St-Hubert, QC J4T 2R4  
Telephone : 1-800-667-0920  
Emergency Phone: : (613) 996-6666

Product use : Admixture

**Preparation Information**Prepared by: : Sewnauth Raghunandan  
Date: : 02/24/2007  
Telephone : (416) 421-3300**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Light Green. Liquid. May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**Inhalation : May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue.  
Eyes : Vapor and/or mist may cause eye irritation. Direct contact may cause temporary redness and discomfort.  
Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.  
Skin : May cause moderate irritation.**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Repeated overexposure to Ethylene Glycol Butyl Ether may cause hemolysis of the red blood cells leading to possible liver and kidney damage. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung, Liver, Kidney, Nerve, Reproductive



**EUCON SRA - 275 GAL TOTE**

Version 1.3  
 REVISION DATE: 02/24/2007

Print Date 07/03/2007

**SECTION 3 : HAZARDOUS INGREDIENTS**

Chemical Name	CAS-No.	Weight % Range
Glycol ether solvent	112-34-5	> 60.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

**SECTION 4 - FIRST AID MEASURES**

- Get immediate medical attention for any significant overexposure.
- Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5: FIRE / EXPLOSION HAZARDS**

- Flash point : 220 °F, 104 °C
- Method : Pensky-Martens Closed Cup
- Lower explosion limit : 0.85 %(V) Solvent
- Upper explosion limit : 24.6 %(V) Solvent
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form. Nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimize pressure build-up.
- Fire and explosion conditions : Vapor concentrations in enclosed areas may ignite explosively. Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors.

**SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately.

**EUCON SRA - 275 GAL TOTE**

Version 1.3

Print Date 07/03/2007

REVISION DATE: 02/24/2007

Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****Personal protection equipment**

- Respiratory protection** : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection** : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection** : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures** : Use professional judgment in the selection, care, and use. Inspect and replace equipment at regular intervals.
- Engineering measures** : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

No known components with exposure limits.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Physical State** : Liquid
- Form** : Liquid
- Color** : Light Green
- Odor** : Slight Ethereal
- pH** : 6.5 - 8.5
- Vapour pressure** : Not available.
- Vapor density** : Heavier than air
- Melting point/range** : Not available.

**EUCON SRA - 275 GAL TOTE**

Version 1.3

Print Date 07/03/2007

REVISION DATE: 02/24/2007

Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Negligible
Evaporation Rate:	: Not available.
Specific Gravity	: 0.95 +/- 0.01
% Volatile Weight	: 100 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid	: Oxidizing agents.Strong acids.Strong bases.
Stability	: Stable under normal conditions. Avoid welding arcs, flames or other high temperature sources.
Hazardous polymerization	: Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Glycol ether solvent, CAS-No.: 112-34-5	
Acute oral toxicity (LD-50 oral)	6,560 mg/kg ( Rat ) 2,000 mg/kg ( Guinea pig ) 2,200 mg/kg ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - WASTE DISPOSAL CONSIDERATIONS**

Disposal Method	: Dispose according to all applicable regulations (hazardous household waste depot, or as liquid industrial waste for industrial product).
-----------------	--

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**  
All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.



**EUCON SRA - 275 GAL TOTE**

Version 1.3  
 REVISION DATE: 02/24/2007

Print Date 07/03/2007

**Canadian Regulations:**

WHMIS Classification : D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

**Other Regulations:**

Regulatory VOC (less water and exempt solvent) : 950 g/l

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	1
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Sewnauth Raghunandan**

**Legend**

- ACGIH - American Conference of Governmental Hygienists
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System