

KUREZ VOX WHITE PIGMENTED

WHITE PIGMENTED CURING COMPOUND

DESCRIPTION

KUREZ VOX WHITE PIGMENTED is a white pigmented wax emulsion curing compound for new concrete requiring a reflective curing membrane. It maintains adequate moisture in new concrete so that desired properties, such as strength and durability, can develop. This white pigmented formulation also reflects sunlight, helping to keep concrete cool when placed in hot weather.

PRIMARY APPLICATIONS

- Exterior paving
- Walls, columns and highway barriers
- Residential concrete
- Sidewalks, curbs and gutters
- Bridge decks and parapet walls
- Commercial concrete

FEATURES/BENEFITS

- Forms an efficient moisture barrier for optimum curing of concrete
- Helps ensure proper cement hydration
- Zero VOC's
- Designed primarily for exterior applications where sunlight reflectivity is needed
- No odor
- ▲ Can contribute to LEED points

TECHNICAL INFORMATION

Typical Engineering Data

The following results were developed under laboratory conditions.

Drying Time* @ 73°F, 50% RH:1 hour
Foot Traffic:2 to 4 hours
Wheel Traffic:6 to 10 hours
VOC Content:0 g/L
Moisture Loss (ASTM C 156):..... < 0.55 kg/m²

* *Low concrete or air temperatures and/or high relative humidity will extend drying times.*

Appearance: KUREZ VOX WHITE PIGMENTED is a white pigmented liquid. After application and drying, the film is white in appearance.

PACKAGING

KUREZ VOX WHITE PIGMENTED is packaged in 55 gal (208 L) drums and 5 gal (18.9 L) pails.

SHELF LIFE

1 year in original, unopened container.

SPECIFICATIONS/COMPLIANCES

- ASTM C 309, Type 2, Class A
- AASHTO M 148, Type 2, Class A & B
- USDA compliant

COVERAGE

ft²/gal (m²/L)
Smooth Concrete:300 (7.4)
Textured Concrete:200 (4.9)

Coverage will vary depending on surface porosity and texture. **AVOID EXCESSIVE BUILD-UP. THICKER APPLICATIONS MAY LEAD TO DISCOLORATION AND POOR PRODUCT PERFORMANCE.**



The Euclid Chemical Company

19218 Redwood Rd. • Cleveland, OH 44110
Phone: [216] 531-9222 • Toll-free: [800] 321-7628 • Fax: [216] 531-9596
www.euclidchemical.com

An **RPM** Company



DIRECTIONS FOR USE

Surface Preparation: This product is designed for use on fresh concrete only. The concrete surface should first be finished to the desired texture.

Mixing: Agitate before using. Material may separate during long term storage. Mild agitation is recommended before usage.

Application: Apply a uniform coverage by spray or roller application. Product may be sprayed with a hand held “pump-up” sprayer or with an airless industrial sprayer. If roller applied, use a short nap sleeve.

Curing: For the best cure of freshly placed concrete, apply KUREZ VOX WHITE PIGMENTED as soon as possible after finishing operations and/or immediately after the disappearance of the “sheen” of surface moisture.

CLEAN-UP

Clean tools and equipment with warm, soapy water before the KUREZ VOX WHITE PIGMENTED dries.

REMOVAL

May be removed by using EUCO CLEAN & STRIP along with aggressive scrubbing, or by the careful use of a high pressure water spray.

PRECAUTIONS/LIMITATIONS

- This product utilizes wax as a curing medium. Application on smooth troweled concrete may result in significantly increased slipperiness.
- Do not allow containers of product to freeze. Store between 50°F to 100°F (10°C to 38°C).
- For best application results, product temperature should be between 50°F to 100°F (10°C to 38°C) with ambient and surface temperatures between 45°F to 110°F (7°C to 45°C).
- Complete removal is necessary before installing adhesives, carpet, tile, or other coverings.
- Do not subject to rain or water for 12 hours after application.
- Not intended for use on architectural concrete panels unless complete removal is planned.
- Do not thin this product with water or other solvents.
- In all cases, consult the Material Safety Data Sheet before use.

Rev. 6.11

WARRANTY: The Euclid Chemical Company (“Euclid”) solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid’s installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid’s products for the Buyer’s intended purposes.