



OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on November 10, 2017.

The Euclid Chemical Company
3835 State Route 72
Kirkland, IL 60146
815-522-3394

Facility: Kirkland, IL

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Patching Materials			
Tamms Structural Mortar [1] [2] [3]	[4]	CLD 23	CMNT

- [1] Mix ratio is 2.4-3.3 L of water per 50 lb mortar.
- [2] Certified for a 7 day moist cure at 73 +/- 3 degrees and 100% relative humidity followed by a 1-3 day air cure at 73 +/- 3 degrees and 50% relative humidity.
- [3] Certification does not include Duralprep AC primer or Eucobar evaporation retarder.
- [4] Certified for use at a maximum of 50% of the total surface area of 7,000 gallon tanks, 60" diameter pipes, and 4" diameter fittings.

Protective (Barrier) Materials

Trade Designation	Water Contact Size Restriction	Water Contact Temp	Water Contact Material
Coatings - Tank			
Hey'Di K-11/Hey'Di SB [1]	>= 1000 gal.	CLD 23	CMNT
Tamoseal Ultra/Tamoseal Ultra Liquid [1]	>= 1000 gal.	CLD 23	CMNT

- [1] Colors: Gray, white
Number of Coats: 2
Sequence of Coats: N/A
Maximum Field Use Dry Film Thickness (in mils): 60
Maximum Thinner: None
Recoat Cure Time and Temperature: 24 hours at 75°F
Final Cure Time and Temperature: 7 days at 75°F
Special Comments: Apply to concrete at a rate of 0.25 lb. mixed slurry per square foot. Mix 1:5 Hey'Di SB Bonding with water then mix that at 50 lb. Hey'Di K-11 to 2 gallons of mixed SB Bonding.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.