



BOND-CRETE

BONDING PRIMER FOR CEMENTITIOUS OVERLAYS

DESCRIPTION

BOND-CRETE is a high-solids bonding agent that can be used with overlays and micro-toppings for a strong bond and increased durability.

PRIMARY APPLICATIONS

- Overlays & micro-toppings
- Bonding new concrete to existing concrete

FEATURES/BENEFITS

- Increases bond strength to existing concrete
- Improves durability

PACKAGING

BOND-CRETE is packaged in 1 gal (3.8 L) containers and 5 gal (18.9 L) pails.

SHELF LIFE

2 Years in original, unopened container.

COVERAGE

Approximately 150 to 250 ft²/gal (3.69 to 6.14 m²/L) on dense surfaces. Porous surfaces may require more material. Do not exceed 300 ft²/gal (7.3 m²/L).

DIRECTIONS FOR USE

Concrete surfaces must be structurally sound, free of loose or deteriorated concrete and free of dust, dirt, paint, efflorescence, oil and all other contaminants. Remove any loose material and any coatings such as paint, curing agents, and sealers. Increte's Uni-Strip is perfect for removing old coatings. Degrease surface with Increte Systems GREASE-AWAY degreaser using 4-8 fl. Oz. of degreaser to one gallon of water then rinse.

Mechanically abrade the surface to achieve a surface profile equal to CSP 2-3 in accordance with ICRI Guideline 310.2. Properly clean profiled area.

Procedure – Apply BOND-CRETE liberally over entire surface with a roller, making sure not to leave any puddled areas. Let dry before applying overlay. Follow immediately with the overlay installation. Product will be tacky.

NOTE: Extremely porous surfaces may require 2 or 3 coats; allow the first coat to dry completely before applying the second coat.

CLEAN-UP

Clean tools and equipment with detergent and water immediately following use. Clean drips and overspray with water while still wet. Dried BOND-CRETE may require mechanical abrasion for removal.

PRECAUTIONS/LIMITATIONS

- Do not use BOND-CRETE where constant moisture or hydrostatic pressure is present (swimming pools, cisterns or other areas that will be immersed).
- Do not dilute BOND-CRETE.
- Keep from freezing.
- Do not apply to frozen or frost-filled surfaces.
- Do not apply if temperature is below 50 °F (10 °C).
- Store at temperatures between 50 to 90 °F (10 to 32 °C).
- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev. 12.17

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.