



INCRETE LIQUID RELEASE

STAMP-TOOL RELEASING AGENT

PACKAGING

1 gal (3.8 L) and 5 gal (18.9 L) units.

YIELD

Approximately 200 ft² gal (4.9 m² L).

APPEARANCE

Clear liquid

CLEAN UP

No clean up is necessary as this product evaporates

SHELF LIFE

4 years in original, unopened container.

BRIEF OVERVIEW

INCRETE LIQUID RELEASE is a clear liquid-release agent designed for use with INCRETE THIN-CRETE stamped overlay systems, stamped concrete or anywhere powdered release agents are impractical to use. This release agent conditions the stamping tool and prevents it from sticking to concrete allowing for the best possible imprint without pulling up the surface. INCRETE LIQUID RELEASE is odorless and leaves minimal residue on the concrete surface.

PRODUCT CHARACTERISTICS

ADVANTAGES

- No dust
- Colorless
- Clean tool release
- Will not damage stamps
- No residue
- Low odor

PHYSICAL PROPERTIES

- Clear, odorless liquid
- Evaporates completely, leaves no residue

COMMON USES

- Conditions the stamping tool to prevent it from sticking to the concrete
- Stamped concrete
- Stamped overlays
- Vertical stamping

COMMON METHODS

- Spray-able

DIRECTIONS FOR USE

APPLICATION PROCESS

INCRETE LIQUID RELEASE should be sprayed lightly on the under-side of the stamping tool. Before stamping, the concrete or overlay should be allowed to reach an initial set-a spongy but firm surface that is not hard. Once the surface is stamped, remove the stamping tool immediately but carefully and allow the concrete surface to dry. Reapply INCRETE LIQUID RELEASE as needed throughout stamping process.

FINISHING

Because INCRETE LIQUID RELEASE leaves no color, INCRETE ANTIQUING AGENT may be used to create a secondary color to the stamped surface. Consult technical data sheets for application procedures and safety precautions.

PRECAUTIONS/LIMITATIONS

- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev. 07.21

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.