



EUCLID CHEMICAL

INCRETE SINGLE COMPONENT FINE SPRAY-DECK GROUT

Polymer-Modified Cementitious Coating

Description

INCRETE SINGLE-COMPONENT FINE SPRAY-DECK GROUT is a pre-blended cementitious coating, and is an ideal horizontal or vertical cover-up for unsightly existing concrete and masonry. **INCRETE SINGLE-COMPONENT FINE SPRAY-DECK GROUT** produces a smooth-finish surface.

Primary Applications

- Pool decks
- Shopping centers
- Walkways
- Residential and commercial entrances
- Patio decks
- Plazas
- Showroom floors
- Vertical applications

Features

- One component, easy to mix and use
- Durable, wear-resistant
- May be integrally colored
- Interior or exterior use
- Trowel, squeegee or spray apply
- May be Stained

Packaging

INCRETE SINGLE-COMPONENT FINE SPRAY-DECK GROUT is available in a 50 lb (22.7 kg) bag.

Shelf Life

1 Year in original, unopened packaging.

Coverage

One bag of **INCRETE SINGLE COMPONENT FINE SPRAY-DECK GROUT** will cover 150 ft² (13.9 m²) for a skim coat, 75 ft² (6.96 m²) for a final coat. The average coverage can vary greatly depending upon the application process and the porosity of the surface. A test area is recommended to determine coverage rate and project requirements

Directions for Use

For complete detailed instructions, consult INCRETE SPRAY-DECK/TEXTURE-CRETE Installation Instructions.

APPLICATION PROCESS

Surface Preparation: Concrete surfaces must be structurally sound, free of loose or deteriorated concrete and free of dust, dirt, paint, efflorescence, oil and all other contaminants. Remove any loose material and any coatings such as paint, curing agents, and sealers. INCRETE UNI-STRIPP is perfect for removing old coatings. Clean surface with a cleaner/degreaser specifically designed for concrete and paver surfaces.

Mechanically abrade the surface to achieve a surface profile equal to CSP 2-3 in accordance with ICRI Guideline 310.2. Properly clean profiled area.

Mixing: Add 4 to 6 qt (3.8 to 5.4 L) of clean, potable, cold water to a clean 5 gal (18.9 L) pail plastic pail. Begin mixing while slowly adding one 50 lb (22.7 kg) bag of INCRETE SINGLE-COMPONENT FINE SPRAY-DECK GROUT. Continue mixing for 2 to 3 minutes.

Application: The grout can then be troweled, squeegeed, or sprayed on the surface at a thickness not to exceed 1/4 in (6.35 mm).

Seal: After at least 24 hours drying time, the surface must be scraped, broomed, and blown with a high velocity blower and then sealed with INCRETE CLEAR SEAL or INCRETE CONCRETE STAIN SEALER. INCRETE SHUR-GRIP may be added to the sealer for additional slip resistance.

MAINTENANCE

Sweep surface as necessary. Wash surface with a mild soap/detergent and rinse with water. Clean surface with a cleaner/degreaser specifically designed for concrete and paver surfaces.

Precautions/Limitations

- Protect surrounding areas and surfaces from overspray.
- For professional use only.
- In all cases, consult the Safety Data Sheet before use.

Rev. 04.20

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.