

INCRETE SINGLE COMPONENT SPRAY-DECK GROUT

POLYMER-MODIFIED CEMENTITIOUS COATING



EUCLID CHEMICAL

PACKAGING

50 lb (22.7 kg) bags

YIELD

Up to 75 ft² for a skim coat and up to 150 ft² for a spray down coat.

MINIMUM/MAXIMUM APPLICATION THICKNESS

Max: 1/4 in (6.35 mm)

APPEARANCE

White powder, can be colored with INCRETE COLOR PACKS

CLEAN UP

Use soap and water before product sets.

SHELF LIFE

1 year in original, unopened package

BRIEF OVERVIEW

INCRETE SINGLE-COMPONENT SPRAY-DECK GROUT is a pre-blended cementitious coating, and is an ideal horizontal or vertical cover-up for unsightly existing concrete and masonry. It can be troweled down or sprayed using a hopper and gun resulting in a variety of decorative finishes adding interest and beauty to a concrete surface. INCRETE SINGLE-COMPONENT SPRAY-DECK GROUT is uniquely formulated with fine aggregate that transforms concrete or masonry substrates into a non-slip, textured surface.

PRODUCT CHARACTERISTICS

ADVANTAGES

- One-component, easy to mix and use
- Durable, wear-resistant
- May be integrally colored with INCRETE COLOR PACKS
- Interior or exterior use
- Can be stained with a variety of Increte stains

COMMON USES

- Pool decks
- Shopping centers
- Walkways
- Residential / commercial entrances
- Patio decks
- Plazas
- Showroom floors
- Vertical applications

COMMON APPLICATION METHODS

- Trowel
- Squeegee
- Sprayer

DIRECTIONS FOR USE

For complete detailed instructions, consult INCRETE SPRAY-DECK/TEXTURE-CRETE Installation Instructions.

SURFACE PREPARATION

Concrete surfaces must be structurally sound, free of loose or deteriorated concrete and free of dust, dirt, paint, efflorescence, oil and all other contaminants. Remove any loose material and any coatings such as paint, curing agents, and sealers. INCRETE UNI-STRIPP is perfect for removing old coatings. Clean surface with a cleaner/degreaser specifically designed for concrete and paver surfaces. Mechanically abrade the surface to achieve a surface profile equal to CSP 2-3 in accordance with ICRI Guideline 310.2. Properly clean profiled area.

MIXING

Add 4 to 6 qt (3.8 to 5.4 L) of clean, potable, cold water to a clean 5 gal (18.9 L) pail plastic pail. Begin mixing while slowly adding one 50 lb (22.7 kg) bag of INCRETE SINGLE-COMPONENT SPRAY-DECK GROUT. Continue mixing for 2 to 3 minutes.

DIRECTIONS FOR USE CONT.

APPLICATION

The grout can then be troweled, squeegeed, or sprayed on the surface at a thickness not to exceed 1/4 in (6.35 mm).

SEAL

After at least 24 hours drying time, the surface must be scraped, broomed, and blown with a high velocity blower and then sealed with INCRETE CLEAR SEAL or INCRETE CONCRETE STAIN SEALER. INCRETE SHUR-GRIP may be added to the sealer for additional slip resistance.

MAINTENANCE

Sweep surface as necessary. Wash surface with a mild soap/detergent and rinse with water. Use a cleaner/degreaser specifically designed for concrete and paver surfaces as needed.

PRECAUTIONS/LIMITATIONS

- Protect surrounding areas and surfaces from overspray
- For professional use only
- In all cases, consult the Safety Data Sheet before use

Rev. 08.21

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.